

**2020**

**Virginia Department of Transportation  
Daily Traffic Volume Estimates  
Including Vehicle Classification Estimates**

where available

**Special Locality Report**

**113**

City of Galax

Information in this report is included in Report

**17**

(Carroll County)

Prepared By

**Virginia Department of Transportation  
Traffic Engineering Division**

In Cooperation With

**U.S. Department of Transportation  
Federal Highway Administration**

The reported 2020 AADTs represent the best estimate of 2020 average daily traffic, however, this year's AADTs do vary from normal traffic in the years prior to 2020 due to COVID-19. The reported AADTs may not represent typical traffic for a given day or period within the year as the drastic seasonal variations were normalized through the factoring process. The 2020 publications are therefore colored to draw users attention to the fact that uses of the 2020 published estimates versus alternative data sources should be determined at users' discretion based on the objectives or nature of the analyses being performed.

The estimated 2020 DVMT for the entire state maintained network total to 208,000,000, which has trended down by 11 percent compared to the 2019 level of 234,000,000. For most traffic links across the state, the estimated 2020 AADTs are also seen to have decreased from their 2019 levels.

Virginia Department of Transportation  
Traffic Engineering Division  
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled “Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes” includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled “Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99”.

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

## Publication Notes

### Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a “Combined Traffic Estimates for Parallel Roadways on this Route” or “Combined Traffic” identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate “NA” for not available.

---

VDOT’s traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating “NA” for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate “NA” for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

## Glossary of Terms:

**Route:** The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

**Length:** Length of the traffic segment in miles.

**AADT:** Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

### QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

**4Tire:** Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

**Bus:** Percentage of the traffic volume made up of buses.

**2Axle Truck:** Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

**3+Axle Truck:** Percentage of the traffic volume made up of single unit trucks with three or more axles.

**1Trail Truck:** Percentage of the traffic volume made up of units with a single trailer.

**2Trail Truck:** Percentage of the traffic volume made up of units with more than one trailer.

### QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

**K Factor:** The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

**QK:** Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

**Dir Factor:** The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

**AAWDT:** Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

**QW:** Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

**Year:** Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

# Route Shield Legend

## Route Systems



Interstate Route

Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.



US Route



Virginia State Route



Frontage Road (F precedes frontage route number)



Secondary Route

## Special Routes



Bus - Business Route  
Bypass - Bypass Route



Truck - Truck Route  
ALT - Alternate Route  
Wve - Wve Route connector



P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.



The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation  
Traffic Engineering Division  
2020  
Annual Average Daily Traffic Volume Estimates By Section of Route  
City of Galax

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
From: WCL Galax To: Reserve Blvd	City of Galax	0.47	7500	G	96%	0%	1%	1%	2%	0%	C	0.094	F	0.537	8200	G
From: Greenville Rd W Stuart Dr To: Reserve Blvd; W Stuart Dr	City of Galax	1.10	6600	G	96%	0%	1%	1%	2%	0%	F	0.084	F	0.556	7100	G
From: Fries Rd To: W Stuart Dr	City of Galax	0.20	9900	G	96%	0%	1%	1%	2%	0%	F	0.088	F	0.574	11000	G
From: SR 89 Main St To: E Stuart Dr	City of Galax	0.34	12000	G	96%	0%	1%	1%	3%	0%	F	0.094	F	0.533	13000	G
From: Meadow St To: E Stuart Dr	City of Galax	1.81	16000	G	96%	0%	1%	1%	3%	0%	F	0.078	F	0.504	17000	G
From: Haynes Rd To: E Stuart Dr	City of Galax	1.10	13000	G	96%	0%	1%	1%	3%	0%	C	0.079	F	0.54	14000	G
From: ECL Galax To: Main St	City of Galax	1.26	5200	G	98%	0%	1%	0%	1%	0%	C	0.091	F	0.566	5600	G
From: SR 97 Pipers Gap Rd To: Main St	City of Galax	0.90	5400	G	99%	0%	1%	0%	0%	0%	C	0.086	F	0.559	5800	G
From: Maroon Tide Dr To: Main St	City of Galax	0.16	4200	G	99%	0%	1%	0%	0%	0%	F	0.083	F	0.564	4600	G
From: Oldtown St To: Main St	City of Galax	0.64	2600	G	98%	1%	1%	0%	0%	0%	C	0.102	F	0.561	2800	G
From: US 58 Stuart Dr To: Pipers Gap Rd	City of Galax	0.11	2200	G	99%	0%	0%	0%	0%	0%	C	0.095	F	0.611	2300	G
From: SR 89 Main St To: Reserve Blvd	City of Galax	0.47	7500	G	96%	0%	1%	1%	2%	0%	C	0.094	F	0.537	8200	G
From: Oldtown Rd To: Reserve Blvd; W Stuart Dr	City of Galax	1.10	6600	G	96%	0%	1%	1%	2%	0%	F	0.084	F	0.556	7100	G
From: Fries Rd To: W Stuart Dr	City of Galax	0.20	9900	G	96%	0%	1%	1%	2%	0%	F	0.088	F	0.574	11000	G
From: SR 89 MAIN ST To: E Stuart Dr	City of Galax	0.34	12000	G	96%	0%	1%	1%	3%	0%	F	0.094	F	0.533	13000	G
From: Meadow St To: E Stuart Dr	City of Galax	1.81	16000	G	96%	0%	1%	1%	3%	0%	F	0.078	F	0.504	17000	G
From: Haynes Rd To: E Stuart Dr	City of Galax	1.10	13000	G	96%	0%	1%	1%	3%	0%	C	0.079	F	0.54	14000	G
From: ECL Galax																



Virginia Department of Transportation  
Traffic Engineering Division  
2020  
Annual Average Daily Traffic Volume Estimates By Section of Route  
City of Galax

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year	
						2Axle	3+Axle	1Trail	2Trail								
<b>City of Galax</b>																	
(2) Calhoun St		1400	G	96%	2%	2%	0%	0%	0%	F	0.090	F	0.552	1600	G	2020	
						From: Jefferson St											
						To: SR 89 Main St											
(3) Fries Rd		870	G	99%	0%	1%	0%	0%	0%	C	0.082	F	0.629	950	G	2020	
						From: US 58 Stuart Dr											
(3) Fries Rd		1100	G	99%	0%	1%	0%	0%	0%	F	0.097	F	0.588	1200	G	2020	
						From: Sherry Lane											
						To: NCL Galax											
(4) Iron Bridge Rd		820	G	98%	0%	1%	1%	0%	0%	F	0.108	F	0.586	890	G	2020	
						From: 113-3 Fries Rd, Leonard Rd											
						To: 38-607 NCL Galax											
(4051) Branch St/Chestnut Dr		500	G	98%	0%	1%	1%	0%	0%	C	0.121	F	0.582	540	G	2020	
						From: SCL Galax											
						To: SR 89 Main St											
(4052) Greenville Rd		820	G	99%	0%	0%	0%	0%	0%	C	0.097	F	0.558	890	G	2020	
						From: WCL Galax											
						To: US 58											
(4052) Stuart Dr		3000	G	98%	0%	1%	1%	0%	0%	F	0.099	F	0.501	3300	G	2020	
						From: US 58 Bypass											
						To: Alderman St											
(4052) Stuart Dr		3200	G	98%	0%	1%	1%	0%	0%	F	0.099	F	0.514	3500	G	2020	
						From: Stanford St											
						To: US 58; W Stuart Dr											
(4052) Mac Arthur St		2300	G	98%	0%	1%	1%	0%	0%	C	0.082	F	0.542	2500	G	2020	
						From: Circle Dr											
(4052) Mac Arthur St		2100	G	98%	0%	1%	1%	0%	0%	F	0.09	F	0.564	2300	G	2020	
						To: SR 89 Main St											
(4053) Lineberry Rd		4100	G	98%	0%	1%	0%	1%	0%	C	0.089	F	0.564	4400	G	2020	
						From: SR 89 Main St											
						To: 113-4056 Poplar Knob Rd											
(4053) Meadow St		7000	G	98%	0%	1%	0%	1%	0%	F	0.087	F	0.502	7600	G	2020	
						From: Grayson St											
						To: US 58 E Stuart Dr											
(4054) Grayson St		1900	G	98%	0%	1%	1%	1%	0%	C	0.112	F	0.596	2000	G	2020	
						From: 113-4055 Jefferson St											
						To: 113-4053 Meadow St											
(4055) Jefferson St		450	G	97%	0%	2%	0%	0%	0%	F	0.130	F	0.5	490	G	2020	
						From: Calhoun St											
						To: Grayson St											
(4055) Jefferson St		870	G	97%	0%	2%	0%	0%	0%	C	0.113	F	0.701	940	G	2020	
						From: US 58 Stuart Dr											
						To: Meadow St											
(4056) Poplar Knob Rd		1700	G	99%	0%	0%	0%	0%	0%	C	0.095	F	0.590	1900	G	2020	
						From: Oak St											
						To: ECL Galax											
(4057) Country Club Lane		910	G	100%	0%	0%	0%	0%	0%	F	0.099	F	0.534	990	G	2020	
						From: SECL Galax											
						To: Poplar Knob Rd											
(4057) Country Club Lane		2300	G	100%	0%	0%	0%	0%	0%	C	0.096	F	0.543	2500	G	2020	
						From: US 58 E Stuart Dr											
						To: Glendale Rd											
(4057) Larkspur Lane		1100	G	100%	0%	0%	0%	0%	0%	F	0.093	F	0.550	1200	G	2020	
						From: US 58 E Stuart Dr											
						To: Cliffview Rd											
(4058) Glendale Rd		6100	G	98%	0%	0%	1%	0%	0%	F	0.094	F	0.614	6600	G	2020	

Virginia Department of Transportation  
 Traffic Engineering Division  
 2020  
 Annual Average Daily Traffic Volume Estimates By Section of Route  
 City of Galax

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
<b>City of Galax</b>																
(4058) Glendale Rd		5600	G	98%	0%	0%	1%	0%	0%	C	0.099	F	0.536	6100	G	2020
(4058) Glendale Rd		3400	G	98%	0%	0%	1%	0%	0%	F	0.092	F	0.531	3700	G	2020
(4059) Cliffview Rd		3700	G	98%	0%	1%	1%	1%	0%	C	0.092	F	0.606	4000	G	2020
(4060) Cranberry Rd		3300	G	98%	0%	1%	0%	1%	0%	C	0.094	F	0.574	3500	G	2020
(4060) Cranberry Rd		1800	G	98%	0%	1%	0%	1%	0%	F	0.101	F	0.609	2000	G	2020
Calloway St		210	G								0.122	F	0.633	220	G	2020
Clover St		920	G								0.12	F	0.606	1000	G	2020
Forrest Ave		90	G								0.157	F	0.522	100	G	2020
Hospital Dr		2700	G	99%	0%	1%	0%	0%	0%	C	0.087	F	0.613	2700	G	2020
Kenbrook Dr		200	G								0.111	F	0.5	220	G	2020
Valley St		4000	G	99%	0%	1%	0%	0%	0%	C	0.087	F	0.587	4000	G	2020
Valley St		1100	G	97%	1%	1%	0%	1%	0%	C	0.099	F	0.659	1100	G	2020